



ZI 12 Ceramic Wool Gasket KF

This is an asbestos-free gasket with adhesive properties on one side. In view of the outstanding biological solubility properties of the used glass fibers, this gasket has been classified as non-carcinogenic. There is consequently no danger classification for this product.

CAUTION: Please note that this type of gasket must be replaced as soon as the part it has been applied to has been opened or operated (access doors, SR joining clips, rectangular and circular duct connections, etc.)

Material	Self-adhesive, asbestos-free, high-temperature glass fibers.
Fiber Diameter	3,2 µm
Operating Temperature	+1100°C (+2012°F)
Tensile Strength	> 350 kPa
Adhesive	Acrylat-Dispersion, solvents-free
Adhesive Support	Formed fabric
Protective Foil	PE silicone foil
Fire	French Norm 110
Food Industry	Not allowed.
Oils	Not resistant. The rock wool fibers themselves are resistant to oil. The presence of oil however would infiltrate all fibers and thus change the physical and chemical characteristics of the gasket. Under such conditions the sealant might and its adhesive will cease to perform normally and their resistance and properties would be greatly diminished / impaired.

Disclaimer:

Every effort has been made to ensure that the information contained in this document is correct, but no warranty can be given in this respect and the company cannot be held liable as a result of any inaccuracy. The client and/or user has the obligation to make sure that the product is suitable for its individual case of application. Free translation: the original documents being in German, the English translation may contain some errors. Products and/or product specifications are subject to change without prior notice.